


Specification for Electric City Bus



Specification for Electric City Bus			
Bus specification	Model	6680BEV	
	Length (mm)	6800	
	Width (mm)	2270	
	Height (mm)	2952	
	Wheelbase (mm)	3700	
	Max. Passengers	37/22 (21+1)	
	Max. Speed (km/h)	≤69	
	Battery capacity	62.2KW.H	
	Announcementendurance mileage	120	
Chassis system	Item	Standard configuration	Remark
	Front axle	CV-HS 3.5T	
	Rear Axle	CV-HS 5T	
	Suspension system	spring suspension (Front 3/rear 4)	
	Steering system	Domestic hydraulic power	
	Brake system	Dual-circuit air brake system, front disc, rear drum, Domestic valve	
	ABS	Guangzhou Kemi ABS	
	Rims	6.0 × 17.5 steel rims	
	Tire	DOUBLE COIN 215/75R17.5	
	Steering	Guangdong Jiangmen	
	Centralized lubrication	Not Equipped	
Wheel cover	Not Equipped		
Vehicle Body system	Floor leather	Flame retardant floor leather	
	Side windows	Built-in sliding window	
	Compartment door	Aluminum	
	Air ventilator	One air ventilator with roof hatch	
	Passenger door	Pneumatic single-swing passenger door (front, middle)	
	Driver seat	Mechanical six-way and backrest adjustable driver	
	Passenger seat	City bus passenger seats	
	Sunshade	Driver side window and sunshade and windscreen sunshade	
	Curtains	Passengers vertical folding sunshade	
	Handrail assembly	Steel handrail	
	Hanging ring	Equipped	
	Air passage	Linen air passage	
	Safety hammer	4 with alarm safety hammer	
	Passenger exit door bell	Equipped	
Tooling box	Equipped, 2 tooling boxes		
Paint	Domestic color paint		
Electrical configuration	Fire extinguisher	Automatic fire extinguishing device for high pressure compartment and battery compartment, 2*4kg Dry powder fire extinguisher	
	Coin Machine	not Equipped	
	Storage battery	Maintenance free battery, 2*100AH	
	Tachograph	Not equipped	
	Digital clock	Equipped	
	High position brake lights	Equipped	
	Audiovisual systems	MP3 player	
	Reversing Monitor	Instrument comes with display function (Middle door+reversing)	
	Heater	No water heating, with electric defrost	
	A/C	SKYWORTH Cold and warm air conditioner, 12000kcal	
	CAN Instrument	Equipped	
Road sign	Front, rear Light box signs		
New energy	Power battery	62.2KWh (Skywell)	
	Motor	PMSM : ,60/110KW, 1000N.M, 3500rpm	
	transmission	Not Equipped	

configuration	Inverter	Hhuichuan four in one	
	Electric air pump	Standard (PMSM)	
	Electric power pump unit	Quanxing Seiko electric steering pump (PMSM)	

