

Price (FOB Shanghai):**US\$19,535****PROFILE****Detailed specifications****ZEVQC-120/750-U2**

Appearance structure	Box material	white metal body, outdoor special paint
	size (W*L*H)(mm)	590*820*1840
	Gross weight KG	502
	Installation method	floor stand
	Inline method	lower wiring patter
	Cable length	7m
Electrical indicators	Input voltage	AC380V±10%
	Rated frequency	50±1Hz
	Power factor	≥0.99
	THDi	≤5%
	Rated power	120KW
	Rated current adjustable 10%-110%	0-200A
	Output voltage range	200-750V
	Charging interface	1/2/3/4 (plugs)
	Steady flow accuracy	≤±1%
	Voltage regulation accuracy	≤±0.5%
	ripple ratio	≤0.5%
	Current-unbalance	≤5%
	Working mode	cycle charging or simultaneous charging (multi charging interface)
Versatility	GB/T CCS Chademo meet	
Function	APP control	provide services such as search, query, booking charge, APP, WeChat,Alipay payment and so on
	Human-machine interface	7-inch LCD display touch screen
	Measurement function	DC measurement
	CAN communication	yes
	Cloud platform monitoring	yes
Security	Overcurrent protection	yes
	Short circuit protection	yes
	Overvoltage and undervoltage protection	yes
	Overheat protection	yes
	Reverse protection	yes
	Plug out power-off protection	yes
	Full charge auto power-off protection	yes
Environmental indicators	Operating efficiency	≥94%
	Operating temperature	-20~50℃
	Storage temperature	-40~70℃
	Operating humidity	5~95% no frost
	Operating altitude	≤2000m
	Noise	≤65dB